

>185.65546 67616.12287 577
>198.65546 65612.23282 955
>198.65546 65612.23282 955
>152.698016 68818.28239 92356
>198.643636 78617.73228 783
>124.634546 78672.23779 683
>458.11142 83417.73237 876
>145.523286 64486.22289 986
>140.77060 32814.07706 328 56-20

MODEL 9311A



Multiple Value DC Current Shunt

- 9 Current Ranges
- 0.1mA to 300A
- Accuracy's to <0.01%
- Improved TC < 3 ppm/°C
- Rack or Bench top Use

MODEL INFORMATION

The Model 9311A Multiple Value DC Current Shunt is the latest development from Measurements International's series of DC resistors and shunts. After many years of research in low value resistance materials, the Model 9311A insures that you get the best performance on the market today. Combined with MI's experience in automated measurements at high current levels, accuracies approaching <0.01% can be achieved at full power.

The process selected in treating the element insures the best performance without introducing self-heating errors with

improved temperature coefficients. The elements are supported on an insulating base for mechanical stability and covered with perforated metal to allow for proper cooling.

Special consideration has been given to the process of curing the elements and reducing the overall temperature coefficient. Optimum surface area dissipates the maximum specified power. The Model 9311A maybe used as a current shunt or as a set of standard resistors. The Model 9311A is used in an air environment.

Specifications:

Selected Resistance	Max Current	Nominal Current	Accuracy
10,000Ω	0.003 Amps	0.00001 Amps	± 0.001%
1,00Ω	0.010 Amps	0.0001 Amps	± 0.001%
100Ω	0.030 Amps	0.001 Amps	± 0.001%
10Ω	0.100 Amps	0.01 Amps	± 0.001%
1Ω	0.300 Amps	0.1 Amps	± 0.001%
0.1Ω	1.500 Amps	1.0 Amps	± 0.001%
0.01Ω	15.00 Amps	10 Amps	± 0.005%
0.001Ω	140.0 Amps	100 Amps	± 0.020%
0.000333Ω	420.0 Amps	300 Amps	± 0.040%
Accuracy:	Calibrated at 23°C - Traceable to NRC and NIST		
Stability:	1 Year - 10 ppm		
Temp Coefficient:	< 3ppm/°C		
Power Coefficient:	< 4ppm/watt in Air		
Operating	18 to 34°C, 10 to 80% RH		
Warranty	1 Year Parts & Labor		

Dimensions

480 x 220 x 300 mm

Weight:

9 kg

Shipping Weight:

11.5 kg

Accessories:

Operating Voltage:

N/A

How to Order:

Model 9311A

Multiple Value DC Current Shunt

Disributed By:

Form MI 66, Rev. 8, Dated 2012-03-28 (QAP19, App. "N")

Data Subject to Change - Rev. 2

Corporate Headquarters

Measurements International
 PO Box 2359, 118 Commerce Drive
 Prescott, Ontario, Canada K0E 1T0
 Phone: (613) 925-5934
 Fax: (613) 925-1195
 Email: sales@mintl.com

Toll Free: 1-800-324-4988

Worldwide Offices

MI-USA

Phone: (407) 706-0328
 Fax: (407) 706-0318
 Email: sales@mintl.com
 Toll Free: 1-866-684-6393

MI-China

Phone: 86-10-64459890
 Fax: 86-10-64459871
 Email: sales@mintl.com

MI-Europe

Phone: (420) 731-440-663
 Fax: (420) 572-572-358
 Email: sales@mintl.com



www.mintl.com